

IN THE CLAIMS:

1. (Currently Amended) An organic electroluminescent device comprising:
at least two or more emitting layers between an anode and a cathode, and
an intermediate electrode layer being interposed between emitting layers,
the intermediate electrode layer being a single layer or a multilayer structure, at least one
of the layers comprising a semiconductive material,
the semiconductive material comprising ~~an acceptor and a donor, wherein the acceptor is~~
~~a at least one~~ conductive oxide comprising a transition metal ~~and is~~ selected from the group
consisting of NbO_x, LaO_x, NdO_x, SmO_x, EuO_x, MoO_x, ReO_x, WO_x, OsO_x, IrO_x and PtO_x,
wherein x is 0.2 to 5, ~~and the donor is an alkali metal and/or an alkaline earth metal.~~

2. – 27. (Cancelled)

28. (Previously Presented) A display comprising a screen comprising the organic
electroluminescent device according to claim 1.

29. – 32. (Cancelled)

33. (Previously Presented) The organic electroluminescent device according to claim 1,
wherein the conductive oxide is MoO_x.

34. (Currently Amended) The organic electroluminescent device according to claim [[1]] 38, wherein the conductive oxide is MoO_x , x is 2 to 3, and the donor is Cs.

35. – 37. (Cancelled)

38. (New) The organic electroluminescent device according to claim 1, wherein the semiconductive material further comprises a donor that is an alkali metal and/or an alkaline earth metal.

39. (New) The organic electroluminescent device according to claim 1, further comprising an electron injecting layer on the anode side of the intermediate layer, wherein the electron injecting layer comprises an alkali metal compound or a reducing dopant.